



OVERVIEW

DEL F 450 is specifically engineered for applications requiring process heating and cooling efficiently between 30°F and 450°F.

Economical and thermally stable, **DEL F 450** heat transfer fluid offers an excellent alternative to costly synthetics and aromatic fluids while delivering precise and efficient cooling down to 30°F.

APPLICATION

DEL F 450 is specifically engineered for applications requiring process heating and cooling efficiently between 30°F and 450°F.

Economical and thermally stable, **DEL F 450** offers an excellent alternative to costly synthetics and aromatic fluids while delivering precise and efficient cooling down to 30°F. **DEL F 450** is an oxidative and thermally stable, high performance, long lasting, environmentally friendly heat transfer fluid. Offering precise temperature control and long life at an economical cost.

THE DIFFERENCE

DEL F 450 heat transfer fluid contains the industries most effective and resilient blend of additives to ensure long-lasting, trouble-free service.

Our exclusive system includes a proprietary, dual stage anti-oxidant and a special blend of metal deactivators, extenders, and other agents that prolong fluid life and help keep systems clean. That also means longer life for parts like pumps and rotary seals.

LASTS LONGER

Oxidation can cripple your system. Left unchecked, it will ultimately cause catastrophic failure and costly downtime. That's why **DEL F 450** heat transfer fluid offers unsurpassed levels of protection against oxidation, and a service life that other fluids simply can't match.

RUNS CLEANER

DEL F 450 heat transfer fluid delivers superior resistance to sludging, a problem plaguing most other fluids. That makes it the best defense against extreme oxidation found in many of today's demanding manufacturing environments, including plastics processing, molding, casting, asphalt, paint, chemical and a wide variety of other applications.

In fact, our exclusive additive technology makes **DEL F 450** heat transfer fluid the perfect solution for all applications, large or small requiring precise temperature control up to 450°F (232°C).

ENVIRONMENTAL

DEL F 450 is environmentally friendly, non-toxic, non-hazardous and non-reportable. It poses no ill effect to worker safety and does not require special handling. After its long service life, **DEL F 450** heat transfer fluid can easily be disposed of with other waste oils.

DEL F 450 PROPERTIES

Appearance: colorless, clear and bright liquid		
Flash Point ASTM D92	302°F	150°C
Fire Point ASTM D92	327°F	163°C
Autoignition ASTM E-659-78	625°F	329°C
Viscosity ASTM D445		
cSt at 104°F / 40°C	8.34	
cSt at 250°F / 121°C	1.69	
cSt at 450°F / 232°C	0.68	
Pour Point ASTM D97	-49°F	-45°C
Density ASTM D1298		
	lb/ft³	g/ml
at 100°F / 38°C	51.4	0.866
at 250°F / 121°C	48.0	0.768
at 450°F / 232°C	43.4	0.722
Average Molecular Weight		
	372	
Carbon Residue ASTM D189	0.005	% Mass
Sulphur Content X-RAY	<.001	weight %
CU Strip Corrosion ASTM D130	1a	
Thermal Expansion Coefficient	0.0564 %/°F	0.1011 %/°C
Thermal Conductivity		
	BTU/hr F ft	W/m.K
at 100°F / 38°C	0.076	0.131
at 250°F / 121°C	0.071	0.124
at 450°F / 232°C	0.066	0.114
Heat Capacity		
	BTU/lb F	kJ/kg K
at 100°F / 38°C	0.549	2.299
at 250°F / 121°C	0.617	2.583
at 450°F / 232°C	0.707	2.959
Vapor Pressure ASTM D2879		
	psi	kPa
at 100°F / 38°C	0.00	0.00
at 250°F / 121°C	0.48	0.07
at 450°F / 232°C	2.28	15.72
Distillation Range ASTM D2887		
	10%	516°F (289°C)
	90%	72°F (411°C)
*Maximum Film Temp.	490°F	254°C
*Maximum Film Temp.	490°F	254°C

The values quoted are typical of normal production. They do not constitute a specification.